




AutoGate

VERTICAL PIVOT LIFT GATE SYSTEMS



The FIRST UL-325 Compliant VPL!

- ◆ GOVERNMENT
- ◆ COMMERCIAL
- ◆ RESIDENTIAL

FEATURES...	BENEFITS...
Meets UL 325 Specifications (2001). Meets CSA Specifications (2011)	Produced to strict standards which provides you with the safest operator possible.
EXTENDED WARRANTY (3 Yrs. Comm./5 Yrs. Res.)	Peace of mind with guaranteed savings.
STAND-ALONE SYSTEM	24VDC power operated – <i>Battery back-up included at no additional charge.</i>
800 PHONE SERVICE	Free calls.
SPACE SAVING	Costly real estate saved.
CUSTOM DESIGN	Increases property value.
ADAPTABLE TO ANY TERRAIN	Curbs -- railroad tracks -- contours
STAND-ALONE 24 VDC GATE ACCESS CONTROL	Continuous security & operation during power outages.
24 VDC RESERVE POWER	1000+ cycles from fully charged batteries <i>(Less when access controls are used).</i>
BUILT-IN BATTERY MAINTAINER	Economical 110 VAC power supply. Maintains battery at peak reserve.
10-12 SECOND OPERATION	Prevents tailgating.
CONTINUOUS DUTY SERVICE	Dependable, worry-free operation in all services.
RUST & CORROSION RESISTANT	20+ years design life. Saves costly replacement.
LOW MAINTENANCE	Requires simple preventative maintenance to keep system functioning properly.

24V VPL Gate Specifications

OPERATOR:	Meets UL 325 Specifications (2001). Meets CSA Specifications (2011).		
OPERATOR CONSTRUCTION:	Frame: 2" Sq., 11 Ga. (.120) Steel Tubing	Mounting Pads: 304 SS	
OPERATOR SIZE:	Skins: 18 Ga. Galvaneal Sheet	Width: 30"	
PAINT:	Type: VPL-24	Length: 68"	Height: 51"
DUTY CYCLE:	Two Part Epoxy Finish. Std Colors: Black, White, Brown, Green & Gray (Custom colors available)		
POWER SUPPLY:	Continuous.		
POWER MAINTENANCE:	120VAC (15 amp) supply, 24v DC powered. (2) 12v Batteries required, NOT included.		
CONTROL CIRCUITRY:	24v Built-In Battery Maintainer "Over-Charge" protection built-in.		
CONTROL WIRING:	Solid state coated Control Board in NEMA 4x weatherproof electrical enclosure.		
GEAR MOTOR:	Sealed Proximity Switches ensure weather & moisture-proof integrity (Boards tested to -40° F).		
OPEN / CLOSING CYCLES:	16 & 18 Ga. single conductor. Copper w/electrolytic copper compression terminals tin-plated for maximum corrosion prevention.		
DELAYED CLOSING:	Horse Power:		
OBSTRUCTION SENSOR:	Bearing Type: 1/3 Gear Type: Hardened Steel		
SEC. BREACH PROTECTION:	Gear Lube: Dextron II E ATF (Rated to -70° F)		
REVERSING EQUIPMENT:	Adjustable from 0 – 60 seconds.		
COMPATIBLE CONTROLS:	Adjustable IRD senses obstructions opening or closing.		
GATE CONSTRUCTION:	24v built-in System Brake when 120v or battery power is present.		
CHAIN LINK CONSTRUCTION:	Optional Reversing/Safety Loop, Leading Reversing Edge, Infrared Reversing Beams, Siren or Optical Operated Sensors.		
GATE LENGTHS:	Keypad, Card Reader, Intercom, Telephone, Wireless & Siren or Optical Operated Sensors.		
GATE HEIGHTS:	2 1/2" Sq., 7Ga. (.187) Aluminum Tubing 21'-24' 2" Sq., 11 Ga. (.120) Steel Tubing over up to 20'		
GATE HARDWARE:	2-3/8", Sch. 40 & Sch. 20 Steel Tubing 9 Ga. Galv. Fabric from 12' up to 22'		
ALUMINUM PICKET CONSTRUCTION:	2-3/8", Sch. 80-Alum., Sch. 40 & Sch. 20 Aluminum Tubing 9 Ga. Alum. Fabric over 22' up to 24'		
STEEL PICKET CONSTRUCTION:	10' – 24' (Consult factory for gates over 24').		
WINDBRACING:	4' – 8' from pad grade. Consult factory for gates over 8' high. (Gates over 8' will require special crating & freight arrangements).		
DOUBLE GATES:	Mounting hardware is 304 Stainless Steel		
SHIPPING WEIGHT:	3/4" Sq. Aluminum Tubing		
WARRANTY:	1/4" Sq. 18 Ga. Galvanized Steel		
	75 mph design, 1/4" aircraft coated cable 16'-20'. Rigid mastid alum over 20'. Control Panel can be set to accommodate 2 nd Operator or Sallie Port with another Operator (Optional Add).		
	Typical VPL-24 Operator with 6' high x 16' long Buckeye style gate = 1,200 lbs. crated weight.		
	Res. = Five (5) Years / Comm. = Three (3) years from date of shipment on manufactured components and workmanship. Purchased components and accessories are covered under their respective warranties (See full Warranty for details).		

The AutoGate Advantage ...



- ◆ Gated Communities
- ◆ Commercial
- ◆ Residential
- ◆ Marinas
- ◆ Mini-Storage
- ◆ Federal, State & Local



Custom gate styles to fit every taste

Innovative designs for distinguished landscapes



20 years of access control technology

Quality products to fit every budget



VPL Gates are carefully designed to give years of safe and reliable operation!



For More Details Contact:



P.O. Box 50 • 7306 Driver Road
Berlin Heights, Ohio 44814

www.AutoGate.com • Email: Sales@AutoGate.com
Phone: 800-944-GATE (4283) • Fax: 419-588-3514

