

POLYRAIL VINYL FENCE SYSTEMS



TRI-MAX PRIVACY FENCE



- Slotted top and bottom rails engineered with angled edges to make panel insertion fast and easy. *Saving you valuable time and money.*
- Standard aluminum I-beam reinforces the bottom rail. *Reinforcement is non-corrosive and prevents sagging bottom rails.*
- Vertical panel features redesigned interlocking concealed fasteners with expandable connections. *Allows adjustment while securely holding the panels together preventing unsightly gaps.*
- Green series co-extrusion process creates strength and helps recycle valuable resources. *Weatherable cap stock includes rails, vertical panels, posts, and side channels.*
- Side channel set with stainless steel screws is shipped inside the top rails. *Field installed to provide a solid attachment with a professional finish eliminating unsightly gaps.*
- 96" centers standard, 60" and 72" fence heights available. *This knock-down system allows us to deliver more product on our truck, which saves you fuel and shipping costs.*



INTERLOCKING FASTENERS



GREEN SERIES CONSTRUCTION



SIDE-CHANNEL ATTACHED TO POSTS WITH STAINLESS SCREWS



Affordable and virtually maintenance-free. Transferable limited lifetime warranty.

POLYRAIL VINYL FENCE SYSTEMS




Interlocking fastener system being installed, can be snapped or slid together. Provides a secure connection between panels.


- Vinyl post 5" x 5" (.130" wall) standard
- 60" fence uses 8' post, 72" fence 9' post, three feet of post anchored into ground
- Slotted top and bottom rail 1-1/2" x 5-1/2" (.080" wall), bottom rail reinforced with aluminum I-beam
- Interlocking vertical panels 1/2" x 11-1/4" (.050" wall)
- Flat post caps standard, gothic or ball caps optional
- All vertical panels factory cut for 7° rackability, racks 12" in 8' standard.
- White and tan colors available



- Gates feature a concealed all-aluminum reinforced frame engineered for strength using stainless steel fasteners. *Gate stays square.*
- Heavy duty aluminum gate post stiffeners (recommended option). *Posts remain rigid for accurate gate closure.*
- Adjustable stainless steel hinge and latch hardware are verified AAMA 2604 Powder Coated. *Hinges are corrosion resistant with easy adjustment for accurate alignment.*
- Stainless steel fastener screws used on gate assembly, hinge, and latch hardware. *Corrosion resistant screws fastened through vinyl and aluminum for positive long-term strength.*



72" TRI-MAX PRIVACY PANEL



60" TRI-MAX PRIVACY PANEL



Quality Products By:



Dynamic • Solutions • Innovation



NAHB

*See website for complete warranty details.

www.diggerspecialties.com

SP03/11 99667

POLYRAIL VINYL FENCE SYSTEMS




Interlocking fastener system being installed, can be snapped or slid together. Provides a secure connection between panels.


- Vinyl post 5" x 5" (.130" wall) standard
- 60" fence uses 8' post, 72" fence 9' post, three feet of post anchored into ground
- Slotted top and bottom rail 1-1/2" x 5-1/2" (.080" wall), bottom rail reinforced with aluminum I-beam
- Interlocking vertical panels 1/2" x 11-1/4" (.050" wall)
- Flat post caps standard, gothic or ball caps optional
- All vertical panels factory cut for 7° rackability, racks 12" in 8' standard.
- White and tan colors available



- Gates feature a concealed all-aluminum reinforced frame engineered for strength using stainless steel fasteners. *Gate stays square.*
- Heavy duty aluminum gate post stiffeners (recommended option). *Posts remain rigid for accurate gate closure.*
- Adjustable stainless steel hinge and latch hardware are verified AAMA 2604 Powder Coated. *Hinges are corrosion resistant with easy adjustment for accurate alignment.*
- Stainless steel fastener screws used on gate assembly, hinge, and latch hardware. *Corrosion resistant screws fastened through vinyl and aluminum for positive long-term strength.*



72" TRI-MAX PRIVACY PANEL



60" TRI-MAX PRIVACY PANEL



Quality Products By:



Distributed By: Allegheny Fence Construction Co., Inc.
4301 Irvine Street; Pittsburgh, PA 15207
Phone) 412-421-6005